

## Description

- Matt
- Water resistant
- High coverage capacity
- Environmentally clean
- Safe for health

## Composition

Acrylic copolymers, polymer additives, pigments, polymer additives, pigments and inorganic fillers

## Recommended use

Designed for exterior construction surfaces: concrete, plaster, cement, brickwork; and interior: gypsum, canvas and gypsum-board.

## Surface preparation

The painted surface must be smooth, solid, dry, clean, moisture and oil free.

## Application

- Stir before use.
- Water can be added about 10% of the total paint mass.
- Apply with a brush, roller or sprayer.
- Apply the paint at air temperature not lower than +5°C .
- Wash the instruments in water when painting is over.
- Dispose of the plastic containers as prescribed by local legislation.

Temperature of the base when applying	from +5°C to +30°C
Coverage per one layer (under laboratory conditions) More precisely, paint consumption depends on the smoothness of the surface.	1 l - 10 m <sup>2</sup>
	5 l - 50 m <sup>2</sup>
	10 l - 100 m <sup>2</sup>
	15 l - 150 m <sup>2</sup>

## Sizes available

5, 10 and 15-liter plastic containers.

## Storage

Keep closed, at temperature no less than +5°C for 24 months after the manufacturing date indicated on the container.

## Attention

- When working in conditions other than normal, the performances may deviate from the ones indicated above.
- The manufacturer bears no responsibility for working in violation of instructions.