

Description

- Transparent
- Resistant to cleaning and mechanical factors

Composition

Alkyd resins, siccatives, white spirit, polymer additives increasing gloss and durability.

Recommended use

Designed for any type of parquet and wooden surfaces.

Surface preparation

The painted surface must be clean, dry and dust, oil free.

Application

- Use for dilution white-spirit or other benzene solvents.
- Apply the lacquer with roller or sprayer.
- The application should be done at the temperature no less than +5°C degrees.
- The lacquer may be applied in two coatings.
- At an ambient temperature +20°C degrees, humidity – 65%, second coating should be executed approximately after 24 hours.
- When the work is over or suspended carefully wash the tools with solvent.
- When the work is over keep the area ventilated.
- Dispose of the metallic containers as prescribed by local legislation.

Temperature of the base when applying	from +5°C to +30°C
Paint consumption per one layer More precisely, paint consumption depends on the smoothness of the coverable surface.	1 l / 8-10 m ²
	3.785 l / 30-38 m ²
	20 l / 160-200 m ²
Final paint drying at an ambient temperature +20°C degree, humidity– 65%	72 hours (3 days)

Sizes available

3,785 liters and 20 liters metallic containers.

Storage

Keep closed, at temperature no less than + 5°C for 12 months after the manufacturing date indicated on the container.

Terms of use

- Keep away from fire.
- Keep away from sunlight.
- Store in a place inaccessible to children.
- When working with big surfaces, protect respiratory organs wearing a protective mask.
- Avoid contact with skin.
- In case of contact with eyes, apply to doctor.

Attention

- When working in conditions other than normal, the performances may deviate from the ones indicated above.
- The manufacturer bears no responsibility for working in violation of instructions.