



Tile Adhesive T3 (Econom)

Description

Composition

Recommended use

Surface preparation

Making the mixture

Application

Sizes available

Storage

Terms of use

Attention

- Gray
- Mineral
- Eco friendly and safe
- Weather resistant

Quartz sand, “Portland” cement, polyvinyl acetate adhesive, extra cellulose additives.

Designed for interior finish works (ceramic tiles, gypsum cardboard, as well as consolidation of substances having firm area).

- Prior to application clean the surface and remove dirt, dust, oil, paint, etc. from the surface.
- Before the beginning of the works (except gypsum cardboard) the surface should be slightly moistened.
- It is recommended to treat the surface with “SHEN” acrylic concentrate.
- Begin the work after 4-5 hours.

- Pour 6,25 - 6,5 l of water per 25kg of dry mixture into a clean container.
- Gradually add dry mixture and stir with a mixer to obtain paste-like mass without lumps.
- Mix the ready mixture after 10 minutes once more and it is ready for use.

- Apply the mixture with a special notched trowel.
- Putty coating thickness not less than 3 mm.
- The works should be done at the temperature no less than +10°C degrees.
- Wash the instruments in water when the work is over.
- Dispose of the paper bags and mixture leftovers as prescribed by local legislation.

Temperature of the base when applying	from +10 °C to +30°C
Amount of water per 1kg of dry mixture	250 - 260 ml
Amount of water per 25kg of dry mixture	6,255 - 6,5 l
Recommended thickness of layer	3mm or more
Time of serviceability of the mixture	3 hours
Dry mixture consumption per 3 mm thick layer More precisely, the consumption depends on the surface quality and thickness of plaster layer.	1 kg / 0,2 m²
	25 kg/ 5 m²

Paper and polypropylene bags. Net weight 25kg.

Store in undamaged packaging, on pallets, in dry premises, at temperatures under 45°C and humidity under 75%, for 6 months after the manufacturing date indicated on the package.

- Store in a place inaccessible to children.
- When working, protect respiratory organs.
- Avoid contact with skin.
- In case of contact with eyes, rinse with clean water and, if needed, apply to doctor.

- It is prohibited to add water into the mixture after its tightening: this can cause decreased mixture adhesion and cracking.
- When working in conditions other than normal, the performances may deviate from the ones indicated in the table.
- The manufacturer bears no responsibility for working in violation of instructions.