

### Description

- Light pink
- Eco friendly
- Outstanding adhesion

### Composition

Acrylic copolymer, polymer additives, inorganic fillers.

### Recommended use

Designed for treatment of smooth concrete surfaces, for creating an adhesive layer between the concrete and refill layers: mortar, grout, stucco.

### Surface preparation

The base surface must be smooth, solid, dry, clean, moisture and oil free.

### Application

- Stir before use.
- Water can be added about 10% of the total mass.
- Apply with a roller or sprayer (with diameter of 1.5 mm) on the solid, weak surface to create an adhesive layer.
- Apply the paint at air temperature not lower than +5°C .
- Wash the instruments in water when painting is over.
- Dispose of the plastic containers as prescribed by local legislation.

Temperature of the base when applying	from +5°C to +30°C
Coverage per one layer (under laboratory conditions) More precisely, paint consumption depends on the smoothness of the surface.	1 l / 3-5 m <sup>2</sup>
	5 l / 15 -25 m <sup>2</sup>
	10 l / 30-50 m <sup>2</sup>
	15 l / 45-75 m <sup>2</sup>

### Sizes available

5, 10 and 15-liter plastic containers.

### Storage

Keep closed, at temperature no less than +5°C for 24 months after the manufacturing date indicated on the container.

### Attention

- When working in conditions other than normal, the performances may deviate from the ones indicated above.
- The manufacturer bears no responsibility for working in violation of instructions.