

Description

- Ecologically clean
- Doesn't contain volatile organic compound
- Low odor
- Matt
- Drying time: 24 hours
- An estimated re-coat time: 4 hours
- Formulated to provide great coverage

Composition

Waterborne, acrylic-composite paint worked out with use of modern technology.

Recommended use

Designed for all internal walls, ceilings and other surfaces. Forms washable matt finish.
You can obtain different tones with tinting machines under color matching system.

Surface preparation

All surfaces must be smooth, clean, dry, free of mildew, grease, sanding dust or other contaminants. Stir thoroughly before use.

Application

- Stir before use.
- Water can be added about 10% of the total paint mass.
- Apply with a brush, roller or sprayer.
- Apply the paint at air temperature not lower than +5°C .
- Wash the instruments in water when painting is over.
- Dispose of the plastic containers as prescribed by local legislation.

Temperature of the base when applying	from +5°C to +30°C
Coverage per one layer (under laboratory conditions) More precisely, paint consumption depends on the smoothness of the surface.	1 l / 14 m ²
	10 l / 140 m ²

Sizes available

10 liter metallic containers.

Storage

Keep closed, at temperature no less than +5°C for 24 months after the manufacturing date indicated on the container.

Attention

- When working in conditions other than normal, the performances may deviate from the ones indicated above.
- The manufacturer bears no responsibility for working in violation of instructions.